

Active Fires Science Processing Algorithm (ACTIVEFIRES_SPA) User's Guide

Version 1.5.08.04

April 2015



**GODDARD SPACE FLIGHT CENTER
GREENBELT, MARYLAND**

Active Fires Science Processing Algorithm

ACTIVEFIRES_SPA

General

The NASA Goddard Space Flight Center's (GSFC) Direct Readout Laboratory (DRL), Code 606.3 developed this software for the International Polar Orbiter Processing Package (IPOPP). IPOPP maximizes the utility of Earth science data for making real-time decisions by giving fast access to instrument data and derivative products from the Suomi National Polar-orbiting Partnership (SNPP), Aqua, and Terra missions and, in the future, the Joint Polar Satellite System (JPSS) mission.

Users must agree to all terms and conditions in the Software Usage Agreement on the DRL Web Portal before downloading this software.

Software and documentation published on the DRL Web Portal may occasionally be updated or modified. The most current versions of DRL software are available at the DRL Web Portal:

<http://directreadout.sci.gsfc.nasa.gov/?id=software>

Questions relating to the contents or status of this software and its documentation should be addressed to the DRL via the Contact DRL mechanism at the DRL Web Portal:

<http://directreadout.sci.gsfc.nasa.gov/?id=dspContent&cid=66>

Algorithm Wrapper Concept

The DRL has developed an algorithm wrapper to provide a common command and execution interface to encapsulate multi-discipline, multi-mission science processing algorithms. The wrapper also provides a structured, standardized technique for packaging new or updated algorithms with minimal effort.

A Science Processing Algorithm (SPA) is defined as a wrapper and its contained algorithm. SPAs will function in a standalone, cross-platform environment to serve the needs of the broad Direct Readout community. Detailed information about SPAs and other DRL technologies is available at the DRL Web Portal.

Software Description

This software package contains the Visible Infrared Imaging Radiometer Suite (VIIRS) Active Fires Science Processing Algorithm (ACTIVEFIRES_SPA). The algorithm takes as inputs VIIRS Moderate Resolution Band Sensor Data Record (SDR) and Terrain-Corrected Geolocation products, and produces the mission-compliant VIIRS Active Fires Application Related Product (ARP), which also contains the Fire Mask (extended capability). The SPA functions in two modes: Standalone, or as an IPOPP plug-in.

Software Version

Version 1.5 of the DRL algorithm wrapper was used to package the SPA described in this document. The Active Fires algorithm has been ported from the Interface Data Processing Segment (IDPS) OPS Version 1.5.08.04.

Enhancements to this SPA include advanced capabilities to meet low latency requirements, available in both Standalone and IPOPP Mode (IPOPP v2.4 or later).

This software will execute on a 64-bit computer and has been tested on computers with 32GB of RAM, with the following operating systems:

- a) Fedora 20 X86_64;
- b) CentOS Linux 7 X86_64;
- c) OpenSUSE Linux 12.1 X86_64;
- d) Kubuntu 14.04 X86_64.

Copyright 1999-2007, United States Government as represented by the Administrator for the National Aeronautics and Space Administration. All Rights Reserved.

Credits

The Active Fires algorithm was provided to the DRL by the JPSS Mission. This algorithm was ported to run outside of the IDPS by the DRL in collaboration with the Land Product Evaluation and Algorithm Test Element (LPEATE).

Prerequisites

To run this package, you must have the Java Development Kit (JDK) or Java Runtime Engine (JRE) (Java 1.6.0_25 or higher) installed on your computer, and have the Java installation bin/ subdirectory in your PATH environment variable. This package contains 64-bit binaries statically pre-compiled on an x86-compatible 64-bit computer running under Fedora 14, using gcc 4.5.1.

Program Inputs and Outputs

The Active Fires algorithm takes as inputs the VIIRS Moderate Resolution Bands M5, M7, M11, M13, M15, and M16 Sensor Data Record (SDR) products and the VIIRS M-Band Terrain-Corrected Geolocation product, and produces the VIIRS Active Fires Application Related Product (ARP) as output.

Installation and Configuration

Installing as a Standalone Application:

Download the ACTIVEFIRES_1.5.08.04_SPA_1.5.tar.gz and ACTIVEFIRES_1.5.08.04_SPA_1.5_testdata.tar.gz (optional) files into the same directory.

Decompress and un-archive the ACTIVEFIRES_1.5.08.04_SPA_1.5.tar.gz and ACTIVEFIRES_1.5.08.04_SPA_1.5_testdata.tar.gz (optional) files:

```
$ tar -xzf ACTIVEFIRES_1.5.08.04_SPA_1.5.tar.gz
$ tar -xzf ACTIVEFIRES_1.5.08.04_SPA_1.5_testdata.tar.gz
```

This will create the following subdirectories:

```
SPA
  ActiveFires
    algorithm
    ancillary
    mode
    station
    testdata
    testscripts
    wrapper
```

Installing into an IPOPP Framework: This SPA can also be installed dynamically into an IPOPP framework to automate production of VIIRS Active Fires ARP data products. The SPA installation process will install SPA service(s) into IPOPP. An SPA service is an IPOPP agent that provides the mechanism necessary for running an SPA automatically within the IPOPP framework. Once this SPA is installed, users must enable the service(s) corresponding to this SPA along with any other Prerequisite service(s). Instructions for installing an SPA and enabling its services are contained in the IPOPP User's Guide (available on the DRL Web Portal). The SPA services associated with this SPA are listed in Appendix A.

Software Package Testing and Validation

The testscripts subdirectory contains test scripts that can be used to verify that your current installation of the SPA is working properly, as described below. Note that the optional ACTIVEFIRES_1.5.08.04_SPA_1.5_testdata.tar.gz file is required to execute these testing procedures.

Step 1: cd into the testscripts directory.

Step 2: There is a script named run-vfm inside the testscripts directory.

To run the Active Fires algorithm, use

```
$ ./run-vfm
```

A successful execution usually requires one minute or more, depending on the speed of your computer and the size of the input. If everything is working properly, the scripts will terminate with a message such as:

Output viirs.vafip is /home/ipopp/drl/SPA/ActiveFires/testdata/output/AVAFO.h5

You can `cd` to the output directory to verify that the science products exist. Test output product(s) are available for comparison in the `testdata/output` directory. These test output product(s) were generated on a 64-bit PC architecture computer running Fedora 14. The output products serve as an indicator of expected program output. Use a comparison utility (such as `diff`, `h5diff`, etc.) to compare your output product(s) to those provided in the `testdata/output` directory. Locally generated files may differ slightly from the provided output files because of differences in machine architecture or operating systems.

If there is a problem and the code terminates abnormally, the problem can be identified using the log files. Log files are automatically generated within the directory used for execution. They start with `stdfile*` and `errfile*`. Other log and intermediate files may be generated automatically within the directory used for execution. They are useful for traceability and debugging purposes. However it is strongly recommended that users clean up log files and intermediate files left behind in the run directory before initiating a fresh execution of the SPA. Intermediate files from a previous run may affect a successive run and produce ambiguous results. Please report any errors that cannot be fixed to the DRL.

Program Operation

In order to run the package using your own input data, you can either use the run scripts within the wrapper subdirectories, or modify the test scripts within the testscripts subdirectory.

To Use the Run Scripts

Identify the 'run' scripts: The wrapper directory within this package contains one subdirectory named `ActiveFires`. The subdirectory contains an executable called `'run'`. Execute `'run'` within the correct wrapper subdirectory to generate the corresponding product. For instance, the `'run'` within `wrapper/ActiveFires` is used for creating Active Fires outputs. Note that to execute `'run'`, you need to have java on your path.

Specify input parameters using <label value> pairs: To execute the `'run'` scripts, you must supply the required input and output parameters. Input and output parameters are usually file paths or other values (e.g., an automatic search flag). Each parameter is specified on the command line by a `<label value>` pair. Labels are simply predefined names for parameters. Each label must be followed by its actual value. Each process has its own set of `<label value>` pairs that must be specified in order for it to execute. Some of these pairs are optional, meaning the process would still be able to execute even if that parameter is not supplied. The two types of `<label value>` pairs that the `ACTIVEFIRES_SPA` uses are:

- a) Input file label/values. These are input file paths. Values are absolute or relative paths to the corresponding input file.
- b) Output file label/values. These are output files that are produced by the SPA. Values are absolute or relative paths of the files you want to generate.

The following tables contain labels, and their descriptions, required by the ACTIVEFIRES_SPA.

| Input File Labels | Description | Source |
|--|---|--|
| viirs.gmtco | VIIRS Moderate Resolution Band Terrain-Corrected Geolocation input HDF5 file path | <ol style="list-style-type: none"> 1. The C-SDR_SPA and VIIRS-SDR_SPA can be used to create these products. 2. Real time VIIRS SDR and Geolocation products over the eastern US region are available from the DRL ftp site at: <a href="ftp://is.sci.gsfc.nasa.gov/gsfcddata/npp/viirs/level1/<SVMxx GMTCO>_npp_dyymmdd_thhmmssS_ehhmmssS*.h5">ftp://is.sci.gsfc.nasa.gov/gsfcddata/npp/viirs/level1/<SVMxx GMTCO>_npp_dyymmdd_thhmmssS_ehhmmssS*.h5 Where yyyy, mm, dd represents the year, month, and day of month for the start of the swath; the first hh, mm, ss, S represents the hour, minutes, seconds, and 10th of a second for the start of the swath and the second hh, mm, ss, S represents the end time of the swath. 3. VIIRS SDR and Geolocation products for other locations and times are available for download at www.class.noaa.gov |
| viirs.svmxx {xx = 05, 07, 11, 13, 15, 16} | VIIRS Moderate Resolution Band Mx {x = 5, 7, 11, 13, 15, 16} SDR input HDF5 file path | |

| Output File Labels | Description |
|--------------------|--|
| viirs.vafip | VIIRS Active Fires Application Related Product (ARP) output HDF5 file path |

Execute the 'run': The following script shows an example of a command line to run the Active Fires algorithm from the testscripts directory:

```
$ ./wrapper/ActiveFires/run \
viirs.gmtco ../testdata/input/GMTCO_npp_d20140901_t1738560_e1740201_b14746_c20140908200702642321_noaa_ops.h5 \
viirs.svm05 ../testdata/input/SVM05_npp_d20140901_t1738560_e1740201_b14746_c20140908200735223402_noaa_ops.h5 \
viirs.svm07 ../testdata/input/SVM07_npp_d20140901_t1738560_e1740201_b14746_c20140908200729256422_noaa_ops.h5 \
viirs.svm11 ../testdata/input/SVM11_npp_d20140901_t1738560_e1740201_b14746_c20140908200858348915_noaa_ops.h5 \
viirs.svm13 ../testdata/input/SVM13_npp_d20140901_t1738560_e1740201_b14746_c20140908200931364181_noaa_ops.h5 \
viirs.svm15 ../testdata/input/SVM15_npp_d20140901_t1738560_e1740201_b14746_c20140908200911898965_noaa_ops.h5 \
viirs.svm16 ../testdata/input/SVM16_npp_d20140901_t1738560_e1740201_b14746_c20140908200729274370_noaa_ops.h5 \
viirs.vafip ../testdata/output/AVAFO.h5
```

A successful execution usually requires 1 minute or more, depending on the speed of your computer and the size of the input. If execution fails, you will see an error message indicating the cause of failure (e.g., a file cannot be found, or a label cannot be recognized). Correct it and run again. If the problem has some other cause, it can be identified using the log files. Log files are automatically generated within the directory used for execution. They start with `stdfile*` and `errfile*` and can be deleted after execution. Other log and intermediate files may be generated automatically within the directory used for execution. They are useful for traceability and debugging purposes. However it is strongly recommended that users clean up log files and intermediate files left behind in the run directory before initiating a fresh execution of the SPA. Intermediate files from a previous run may affect a successive run and produce ambiguous results. The 'run' can be executed from any directory the user chooses. This can be done by prefixing it with the file path for the 'run' script.

NOTES:

1. The data products generated by this SPA may be visualized with the DRL's H2G_SPA (Hierarchical Data Format [HDF] to Georeferenced Tagged Image File Format [GeoTIFF] Converter Science Processing Algorithm). H2G is designed specifically for Direct Readout applications to create geolocated GeoTIFF images, jpeg browse images, and png browse images for parameter datasets in SNPP products and EOS products. H2G_SPA and its User Guide are available for download from the DRL Web Portal. Please refer to Appendix A for information on enabling image production for this SPA in IPOPP.

To Use the Scripts in the testscripts Directory

One simple way to run the algorithms from the directory of your choice using your own data is to copy the `run-vfm` script from the testscripts directory to the selected directory. Change the values of the variables like `WRAPPERHOME`, `INPUTHOME` and `OUTPUTHOME` to reflect the file paths of the wrapper directories and the input/output file paths. Then modify the input/output file name variables. Run the script to process your data.

Appendix A SPA Services

Installation of this SPA in IPOPP mode will make the SPA services listed in Table A-1 available to IPOPP. These services along with any other Prerequisite services (listed in Table A-2) will need to be enabled to allow IPOPP to automate production of the ACTIVEFIRES_SPA data products. Furthermore, users who wish to generate image products from the data products generated by this SPA will need to enable the image-generating services listed in Table A-3. The SPAs containing the Prerequisite and the image-generating services listed in Tables A-2 and A-3 can be downloaded from the DRL Web Portal, in case they are not already available in your IPOPP installation. Details about these other SPAs are available in the respective SPA User's Guide. Please refer to the IPOPP User's Guide for instructions on how to install an SPA in IPOPP and enable the corresponding services.

Table A-1. SPA Services

| Services for this SPA | Data Products produced | |
|-----------------------|------------------------|---|
| ActiveFires | Product Name | Destination (when installed in IPOPP) |
| | VIIRS Active Fires ARP | /raid/pub/gsfcddata/npp/viirs/level2/AVA FO_npp_dyymmdd_thhmmssS_ehh mmssS*.h5* |
| | | |

* Where *yyyy*, *mm*, *dd*, *hh* represents the year, month and day of month for start of swath; the first *hh*, *mm*, *ss*, *S* represents the hour, minutes, seconds and 10th of a second for the start of swath and the second *hh*, *mm*, *ss*, *S* represents the end time of the swath.

Table A-2. Prerequisite Services

| Prerequisite SPA services | SPA in which they are available |
|--------------------------------|---------------------------------|
| VIIRS_C-SDR OR VIIRS-SDR | C-SDR_SPA VIIRS-SDR_SPA |

NOTE: The services VIIRS-SDR and VIIRS_C-SDR must never be run simultaneously.

Table A-3. Image-generating Services

| Image-generating services | SPA in which they are available |
|---------------------------|---------------------------------|
| vfmh5-geotiff | H2G_SPA |

NOTE: Please refer to the H2G_SPA User's Guide for more details about the image products, including their locations and filename patterns when they are generated in IPOPP.